

BA390 panel lamps provide reliable cost effective visual status indication in all hazardous gas and dust areas. Each BA390 lamp produces a bright, uniform output with a typical life greater than ten years. All models contain a 20mA current regulator therefore they consume a constant current and hence have a constant brilliance independent of supply voltage. Protection against excess voltage and reverse connection is included in each lamp.

IECEx and ATEX intrinsic safety certification allows BA390 LED panel lamps to be installed in all gas and dust hazardous areas. Two lamps may be powered from a single IIC intrinsically safe galvanic isolator. FM gas approval allows BA390 lamps to be installed in the USA.

Five well defined lamp colours - red, amber, green, blue and white allow lamps to be selected to comply with the indicator light colours recommended by IEC 73. When not powered, the front of panel coloured diffuser enables the lamp colour to be easily identified.

IP66 sealing of the lamp front and the joint between the lamp and the panel allow the BA390 to be installed in areas that will be hosed, washed or splashed. When rear of panel environmental protection is also required, the optional BA599 rear sealing kit provides IP66

protection and includes a cable gland to seal and support the supply cable.

Mounting is via a single industry standard 22.5mm diameter hole. The lamp housing, fixing nut and terminals have a maximum diameter of 30mm which permits a very high packing density on the panel.

To aid identification from the rear of the panel, the model number and suffix which identifies the colour are marked on the lamp body close to the terminals

Reliability is ensured by an ISO9001 approved quality control system supported by a three year guarantee.

For low current applications complementary BA390S panel lamps, which have the same features and certifications as BA390 lamps, but without a current regulator, can be used with currents as low as 4mA. These lamps are ideal for use with low current sources such as fieldbus multiple output modules. See the BA390S datasheet for details.

For safe area installations, please refer to the BA590 datasheet which describes a range of non certified 24V dc powered panel lamps.

Application Guide AG390 includes additional information about how to use both BA390 and BA390S lamps.

BA390

LED Panel Lamp

Intrinsically safe for use in all gas and dust hazardous areas

- ◆ **Intrinsically safe IECEx, ATEX & FM certification.**
- ◆ **Red, amber, green, blue & white models.**
- ◆ **20mA constant current & brilliance.**
- ◆ **IP66 front**
- ◆ **IIC isolator will power two lamps.**
- ◆ **3 year guarantee**



BEKA

associates

Sales & Support Distributor:-

Stockshed Limited. Stoneycroft House,
Mud Lane, Eversley. Hampshire.
RG27 0QS. U.K. Tel. (0118) 9734955
e-mail info@stockshed.com



SPECIFICATION

Power supply

Voltage	
Operating	14 to 30V dc
Reverse	60V max
Current	18 to 22mA

Output

Lamp colour	Typical illuminance at 150mm
Red	160 lux
Amber	230 lux
Green	230 lux
Blue	530 lux
White	270 lux

Intrinsic Safety

International IECEx

Code	gas	Ex ia IIC T4 Ga
	dust *	Ex ia IIIC T135°C Da -20°C ≤ Ta ≤ +60°C

Input safety parameters

Ui	30V
Ii	159mA
Pi gas	1.2W
Pi dust *	0.683W

Certification number IECEx ITS 08.0030X

Europe ATEX

Code	gas	Group II Category 1G Ex ia IIC T4 Ga
	dust *	Group II Category 1D Ex ia IIIC T135°C Da -20°C ≤ Ta ≤ +60°C

Input safety parameters

Ui	30V
Ii	159mA
Pi gas	1.2W
Pi dust *	0.683W

Certificate numbers ITS13ATEX27822X

* Dust certification is an option

USA FM *only gas certification*

Standard	3610 Entity intrinsic safety
Code	CL I: Div 1: GP A, B, C & D: T4 @ 60°C
	AEx ia IIC T4 Ta = 60°C
File	3022662

Standard	3611 Nonincendive
Code	CL I: Div 2: GP A, B, C & D: T4 @ 60°C
File	3022662



Environmental

Operating temperature	-20 to 60°C
Storage temperature	-40 to 85°C
Relative humidity	5 to 95% non condensing
Operating life	100,000 hours typical
Enclosure Front	IP66
Rear	IP20 - see accessories for BA599 optional IP66 rear sealing kit.
EMC	Complies with EMC Directive 2014/30/EU.


Mechanical

Terminals	Screw clamp for 1.5mm ²
Diffuser material	Polycarbonate
Body material	Nylon 6
Weight	18g


DIMENSIONS (mm)



Fixing centres for maximum packing density.
Special tool may be required to tighten fixing nuts
when minimum spacing is used.



TERMINAL CONNECTIONS



Accessories

Dust certification	IECEx and ATEX dust certification
Rear sealing kit	BA599 provides IP66 protection for terminals and rear of the lamp. Supplied with gland for 7 to 12mm diameter cable.

HOW TO ORDER

Lamp colour

Red
Amber
Green
Blue
White

Please specify

BA390R
BA390A
BA390G
BA390B
BA390W

Accessories

IECEx & ATEX certification
Rear sealing kit

Please specify if required

Dust certification
BA599