

The **BA527E-SS** rugged general purpose, panel mounting 4/20mA loop powered Indicator, has a stainless steel housing allowing it to be safely installed in harsh industrial and marine environments, or where the front of the instrument is likely to be impacted. Incorporating a full 5 digit display plus a 31 segment bargraph with guaranteed performance between -40 and 70°C, the indicator can be calibrated to show the 4/20mA input current in almost any engineering units.

**Main application** of the BA527-SS is to display a measured variable in meaningful engineering units within an industrial process area. The rugged stainless steel housing and robust construction make the BA527E-SS ideal for installation in panel enclosures located in harsh environments such as agricultural vehicles and waste water processing plant. The indicator includes a square root extractor for flow applications, a sixteen point fully adjustable lineariser and a tare function which enable most types of 4/20mA process variables to be displayed in linear units.

The **stainless steel cast front** provides IP66 front of panel ingress protection and a captive silicone gasket seals the joint between the BA527E-SS and the panel enclosure in which it is mounted. The ingress and impact protection provided by the indicator's stainless steel housing, including the 10mm thick glass display window, have been independently tested at maximum and minimum operating temperatures by Intertek Testing and Certification.

A **bold 11mm high 5 digit display and 31 segment bargraph** provides maximum contrast and has a wide viewing angle, allowing the BA327E-SS to be easily read in most lighting conditions over a wide temperature range. An optional factory fitted backlight is available for applications in poorly illuminated areas. The five digits, with four decimal point positions and a negative sign, may be configured to display any variable between -99999 and 99999.

An **optional backlight** which may be loop or separately powered is available as a factory fitted option. It provides green background illumination allowing the display to be read at night or in poorly illuminated areas. When powered from the 4/20mA loop no additional field wiring is required. Powering from a separate supply produces a brighter backlight but requires additional wiring and another power supply.

**Optional dual alarm outputs** which can switch low power loads, such as a sounder, beacon or solenoid valve are available as a factory fitted option. The two galvanically isolated single pole solid state alarm outputs may be independently configured as high or low alarms with normally open or closed outputs. Annunciators on the display show the status of both alarm outputs.

**Units of measurement** may be shown on the scale card which is visible through the window on the right hand side of the display. Instruments are supplied with the units legend requested when ordered, but the scale card may be easily changed on-site without removing the BA527E-SS from the panel enclosure or opening the instrument case.

**Reliability is ensured** by component conformal coating, protection from incorrect connection and from radio frequency interference. The indicator has been subjected to thermal endurance and vibration testing and is supported by a three year guarantee.

**Other rugged models** in this range of loop powered indicators, all of which have a stainless steel enclosure, include the BA507E-SS general purpose indicator which has a similar electrical specification as the BA527E-SS, but has four 15mm high display digits. Intrinsically safe Ex ia and Ex nA 4 and 5 digit models are also included, please see datasheets for the BA307E-SS, BA327E-SS, BA307NE and the BA327NE.

# BA527E-SS

## Rugged 2-wire 4/20mA 5 digit indicator

*General purpose  
for use in harsh  
& marine  
environments*

- ◆ Rugged IP66 stainless steel enclosure.
- ◆ Loop powered only 1.2V drop.
- ◆ 5 digit 11mm high display & 31 segment bargraph.
- ◆ Optional backlight & alarms.
- ◆ Easy on-site scale card installation.
- ◆ Root extractor and 16 segment lineariser.
- ◆ 3 year guarantee

# BEKA


## associates

Sales & Support Distributor:-  
Stockshed Limited. Stoneycroft  
House,  
Mud Lane, Eversley. Hampshire.  
RG27 0QS. U.K. Tel. (0118)  
9734955  
e-mail info@stockshed.com


## SPECIFICATION

<b>Input</b>	
Current	4 to 20mA
Voltage	Less than 1.2V at 20°C Less than 1.3V at -40°C Less than 5V with optional backlight loop powered.
Over range	±200mA or ±30V will not damage the indicator.
<b>Display</b>	
Type	Liquid crystal, non-multiplexed 5 digits 11mm high & 31 segment bargraph.
Span	Adjustable between 0 & ±99999 for a 4/20mA input.
Zero	Adjustable between 0 & ±99999 with 4mA input.
Decimal point	1 of 4 positions or absent
Polarity	Automatic minus sign
Zero blanking	Blanked apart from 0 in front of the decimal point.
Direction	Display may increase or decrease with increasing 4/20mA input.
Reading rate	2 per second
Over range	99999 or -99999 with flashing decimal points.
<b>Push buttons</b>	
▼	Shows display with 4mA input
▲	Shows display with 20mA input
P	Displays input in mA or as a % of span, has a modified function when alarms are fitted.
E	Used for Tare function
<b>Accuracy at 20°C</b>	
Linear	±0.02% of span ±1 digit
Root extracting	±16µA at input ±1 digit
Temperature effect on:	
Zero	Less than 25ppm of span/°C
Span	Less than 50ppm of span/°C
Series mode rejection	Less than 0.05% of span error for 1mA pk to pk 50 or 60Hz interference.
<b>Environmental</b>	
Operating temperature	-40 to 70°C
Storage temperature	-40 to 85°C
Humidity	To 95% at 40°C non-condensing
Vibration	Report available
Enclosure	
Ingress protection	Front IP66, rear IP20
Impact protection	Front 7J, window 4J
Material	Stainless steel BS 3146-2:1977 ANC4B (316)
EMC	Complies with 2004/108/EC
<b>Mechanical</b>	
Terminals	Screw clamp for 0.5 to 1.5mm <sup>2</sup> cable with removable terminal blocks.
Weight	0.85kg
<b>Accessories</b>	
Backlight	Green may be loop or separately powered Indicator input voltage 5V
Loop powered	
Separately powered	
Supply voltage	9 to 30V dc
Supply current	22.5mA at 9 to 30V
Alarms	Two alarm outputs each of which may be independently configured as a high or low alarm contact with a NO or NC output. Isolated solid state switch
Output	
V <sub>max</sub>	30V dc
I <sub>max</sub>	200mA
R <sub>on</sub>	5Ω + 0.7V max
R <sub>off</sub>	1MΩ min
Printed scale card	Blank card fitted to each indicator can be supplied printed with specified units of measurement.
Pack of printed scale cards.	Contains 28 common units of measurement and 2 blank cards.

## DIMENSIONS (mm)



## TERMINAL CONNECTIONS



Tag legend	Specified tag number or application information laser etched onto rear of the instrument.
Support plate	Evenly distributes clamping force when the indicator is installed in a non-metallic or thin panel less than 1mm thick.
BA495 rear cover and sealing kit	Provides impact and IP66 protection for rear of instrument. #

# See accessory datasheet for details

## HOW TO ORDER

Model number	BA527E-SS
Display mode	Linear, root or lineariser*
Display at:	} Include position of decimal point & sign if negative. Together with intermediate points if linearisation is required.*
4.000mA	
20.000mA	
<b>Accessories</b>	
Display backlight	Backlight
Dual alarms	Alarms
Scale card	Legend required
Tag	Legend required
Support plate	Support plate
Rear cover and sealing kit	BA495

\* Will be set to display 0.00 at 4mA and 100.00 at 20mA with a linear display if calibration information is not supplied. Can easily be recalibrated on-site.